

NDRX_ATFORK_PREPARE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	BUGS	5
6	SEE ALSO	6
7	COPYING	7

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
void ndrx_atfork_prepare(void);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

When process is about to copy it self (i.e. perform forking in UNIX terms), Enduro/X requires certain tasks to be performed before this action. Particularly, if System V IPC transport is used by Enduro/X, then auxiliary threads shall be terminated and contexts released. Thus if doing manual **fork()**, then before this call, parent shall call **ndrx_atfork_prepare()** procedure. Procedure can be registered with **pthread_atfork()**, passing it to *prepare* argument.

At given time function does some logic by System V IPC, for other IPC no logic is executed. But this fact is subject of change, and in future releases some other tasks might be required to be one by Enduro/X before process forking, thus it is recommended to use **ndrx_fork()**, call manually **ndrx_atfork_prepare()** or register it with **pthread_atfork()**

Chapter 3

RETURN VALUE

N/A

Chapter 4

ERRORS

N/A

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

`ndrx_fork(3)` `ndrx_atfork_parent(3)` `ndrx_atfork_child(3)`

Chapter 7

COPYING

© Mavimax, Ltd