

TPLOGDELBUFREQFILE(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
int tplogdelbufreqfile(char *data);
```

For XATMI client link with *-latmiclt -latmi -lubf -lnstd -lpthread -lrt -lm*

For XATMI server link with *-latmisrvl -latmisrvnomainl -latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Remove request logging file name from UBF buffer. This basically removes **EX_NREQLOGFILE** field from buffer, if present.

Chapter 3

RETURN VALUE

On success, **tplogdelbufreqfile()** return zero; on error, -1 is returned, with **tperrno** set to indicate the error.

Chapter 4

ERRORS

Note that **tpstrerror()** returns generic error message plus custom message with debug info from last function call.

TPENOENT Filed not present or failed to remove from UBF.

TPEINVAL Not UBF buffer or buffer NULL.

Chapter 5

EXAMPLE

See `atmitest/test031_logging/atmiclt31.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

tplogsetreqfile(3) **tplogsetreqfile_direct(3)** **tplogconfig(3)** **tplogdump(3)** **tplogdumpdiff(3)** **tplog(3)** **ex_devguide(guides)** **ndrxdebug.conf(5)**

Chapter 8

COPYING

© ATR Baltic, SIA