

**BUSED(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<a href="#">1</a>	<a href="#">SYNOPSIS</a>	<a href="#">1</a>
<a href="#">2</a>	<a href="#">DESCRIPTION</a>	<a href="#">2</a>
<a href="#">3</a>	<a href="#">RETURN VALUE</a>	<a href="#">3</a>
<a href="#">4</a>	<a href="#">ERRORS</a>	<a href="#">4</a>
<a href="#">5</a>	<a href="#">EXAMPLE</a>	<a href="#">5</a>
<a href="#">6</a>	<a href="#">BUGS</a>	<a href="#">6</a>
<a href="#">7</a>	<a href="#">SEE ALSO</a>	<a href="#">7</a>
<a href="#">8</a>	<a href="#">COPYING</a>	<a href="#">8</a>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
long Bused (UBFH *p_ub );
```

```
Link with -lubf -lnstd -lm -lpthread
```

## Chapter 2

# DESCRIPTION

Return the number of bytes used in *p\_ub* buffer.

## Chapter 3

# RETURN VALUE

On success, **Bused()** return the number of bytes used; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Bsterror(3) can give more description for error (for last call).

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted. p\_ub is NULL.

## Chapter 5

# EXAMPLE

See `ubftest/test_badd.c` for sample code.



## Chapter 6

# BUGS

Report bugs to [madars.vitolins@gmail.com](mailto:madars.vitolins@gmail.com)

# Chapter 7

# SEE ALSO

**Blen(3)** **Binit(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd