

EX_ENV(5)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	DESCRIPTION	1
2	Mandatory Env. Variables	2
3	EXAMPLE	5
4	BUGS	8
5	SEE ALSO	9
6	AUTHOR	10
7	COPYING	11

Chapter 1

DESCRIPTION

EnduroX use set of environment variables which is initial environment for application domain. There is set of parameters related to system, prefixes, Posix Queue mount points, various system limits. Next step to the configuration is appdomain config it self, in *ndrxconfig.xml* and *debug.conf*.

Chapter 2

Mandatory Env. Variables

NDRX_NODEID=NODE_ID

Cluster Node ID. Should be within 1..32.

NDRX_CLUSTERISED=1|0

Do we work in cluster mode or not? *1* - yes, we are in cluster. *0* - no, we are not in cluster.

NDRX_LDBAL=LOAD_BALANCE_PERCENT

if `LOAD_BALANCE_PERCENT` is 0 = means process all locally, if value is set to 100 = process all on remote servers (if svc available on remote server). 70% means, process 30% locally 70% remotely.

NDRX_TOUT=TIME_OUT_IN_SECONDS

Global `tpcall()` timeout, if not called with `TPNOTIME` flag. If process will not return in this time, then `TPETIME` error will be returned.

NDRX_ULOG=ULOG_PATH

Writable system path where to write user logs.

NDRX_QPREFIX=APP_PREFIX

Prefix used for POSIX IPC resources (shm and queue).

NDRX_SVCMAX=MAX_SERVICES

This determines the maximum number of services supported by instance. The less is number, then less shared memory is used. However for performance reason, number should be much bigger (3-4 times) than actual estimated service count. Bigger number might speed up linear hashing, i.e. it will be less likely that hash will collide.

NDRX_SRVMAX=MAX_SERVERS

Maximum number of servers that will be supported. This affects the `-i` flag. Server ID. The max server id will be `MAX_SERVERS-1`.

NDRX_CONFIG=FULL_PATH_TO_CONFIG_FILE

This shows the full path to usual `ndrxconfig.xml`.

NDRX_QPATH=QUEUE_MOUNT_POINT

Full path to directory where POSIX Queue is mounted.

NDRX_SHMPATH=SHARED_MEM_MOUNT_POINT

Full path to POSIX Shared memory mount point.

NDRX_CMDWAIT=NDRXD_COMMAND_WAIT_SECS

Number of second to wait for commands, after which `ndrxd` does other checks.

NDRX_DPID=PATH_TO_NDRXD_PID_FILE

This is full path to `ndrxd` PID file.

NDRX_RNDK=APP_DOMAIN_RANDOM_KEY

Random key to identify the processes belonging to this app domain (i.e. used in ps ef).

NDRX_IPCKEY=SYS_V_SEMAPHORE_KEY

System V Semaphores key number. Used for shared memory locking. POSIX semaphores are not used here, because they are not unlocked if process dies during acquired semaphore.

NDRX_MSGMAX=MAX_MSGS_PER_QUEUE

Posix queue config attrib. Max number of messages that can be put in one queue.

NDRX_DQMAX=NDRXD_ACCESS_Q_MSG_MAX

EnduroX ATMI daemon *ndrxd* access Q size. Bigger is better.

NDRX_MSGSIZEMAX=NDRXD_ACCESS_Q_MSG_MAX

Max message size (in bytes).

NDRX_APPHOME=FULL_PATH_TO_APPDOMAIN_INSTANCE_DIR

This is full path to application (not an EnduroX directory it self) root directory.

NDRX_HOME=FULL_PATH_TO_ENDUROX_ROOT_DIRECTORY

Full path to EnduroX installation directory.

NDRX_DEBUG_CONF=FULL_PATH_TO_DEBUG_CONFIG_FILE

This sets full path to debug configuration file.

NDRX_UBFMAXFLDS=MAX_NUMBER_OF_UBFFIELDS

Max number of UBF fields. Used for hashing. Bigger number is better. The max number is number is 33554432 (25 bit).

NDRX_DMNLOG=FULL_PATH_TO_NDRX_DMNLOG

The full path to *ndrxd* log file. Used by shell scripts.

NDRX_DMNLEV=LOG_LEVEL_OF_NDRXD

Log level of *ndrxd*. From 1..5. 5 is max. Used by shell scripts.

NDRX_LOG=FULL_PATH_TO_XADMIN_LOG_FILE

Full path to *xadmin* log file. Used by shell scripts.

NDRX_LEV=LOG_LEVEL_OF_XADMIN

Log level of *xadmin*. From 1..5. 5 is max. Used by shell scripts.

NDRX_XA_RES_ID=XA_RESOURCE_ID

XA API two phase commit resource id. Must be set if using distributed transactions.

NDRX_XA_OPEN_STR=XA_OPEN_STRING

This is open string for two phase commit XA driver. Must be set if using distributed transactions.

NDRX_XA_CLOSE_STR=XA_CLOSE_STRING

This is close string for two phase commit XA driver. This is optional, *NDRX_XA_OPEN_STR* will be used if not set.

NDRX_XA_DRIVERLIB=ENDUROX_XA_DRIVER_LIB

This is full path to Enduro/X shared library which loads the XA api.

NDRX_XA_RMLIB=RESOURCE_MANAGER_SPECIFIC_DRIVER

This is full path to resource manager's specific driver (shared library). Must be set if using distributed transactions.

NDRX_XA_LAZY_INIT=LAZY_INIT_FLAG

Set to 1 if XA sub-system should be initialized on first transactions. If not set, then defaulted to 0, meaning initialize XA sub-system on executable startup.

NDRX_NRSEMS=NDRX_NRSEMS

Number of semaphores used for protecting shared memory, when Enduro/X running in *poll()* mode. The minimum is recommended something about 7. Every service name in shared memory is hashed and semaphore protecting the service is calculated by modulus of NRSEMS. This affects *NDRX_IPCKEY* semaphore, by giving the more occurrences in array. The first array entry is used by normal Enduro/X operations, and the others 2..1+NRSEMS is used by *poll()* mode service protection. Default value is 30.

NDRX_MAXSVCSRVS=NDRX_MAXSVCSRVS

Max number of servers can advertise same service. This is used only in *poll()* mode. The number affects the size of shared memory used for services. Bigger number causes more memory to be used for service registry. If the number of servers goes over this number for one service, the service entry will be ignored.

PATH=PATH

This is not Enduro/X specific env variable. But Enduro/X distribution bin directory should be included in system PATH env. variable.

FLDTBLDIR=FULL_OR_RELATIVE_PATH_OF_UBF_FIELD_DIRS

This is directory where .fd files are located. I.e. UBF field definitions.

FIELDTBLS=COMMA_SEPERATED_LIST_OF_FIELD_FILES

This is comma separated list of field files found in FLDTBLDIR.

NDRX_CCONFIG=NDRX_COMMON_CONFIG_FILE

If this is set then, all above configuration is read from specified ini file in *NDRX_COMMON_CONFIG_FILE* in [*@global*] section. The Enduro/X config driving unit is able to merge configuration from multiple config files, and you can set higher priority files by in *NDRX_CCONFIG1*, *NDRX_CCONFIG2*, *NDRX_CCONFIG3*, *NDRX_CCONFIG4*, *NDRX_CCONFIG5*. Basically *NDRX_CCONFIG* is lowest priority and *NDRX_CCONFIG5* is highest priority. The specified configuration file can be directory, in that case Enduro/X will search for files with mask *.ini, *.cfg, *.conf, *.config files. All will be loaded in alphabetical order.

NDRX_CCTAG=NDRX_COMMON_CONFIG_TAG

This is basically subsection used for Enduro/X configuration sections [*@global*], [*@debug*], [*@queue*]. If the variable is set, then Enduro/X will lookup at process startup for sections like [*@global/YOUR_TAG*], etc. CC tag can contain multiple sections, for example *server1/RM2*. Enduro/X will lookup the variables in each section [*@global/server1*] and [*@global/RM2*] for setting up the system.

NDRX_XADMIN_CONFIG=XADMIN_CONFIG_FILE

This variable is used by **xadmin** read the specific configuration file with xadmin's settings. Variable is optional.

HOME=UNIX_USER_HOME_DIR

This variable is used by **xadmin** to search for per user configuration file when xadmin is started. In home directory search for configuration is done by \$HOME/.xadmin.config. This file is used in case if *NDRX_XADMIN_CONFIG* is missing. Variable is optional.

Chapter 3

EXAMPLE

Sample configuration:

```
export FIELDTBLS=Exfields,fieldtab1.fd,fieldtab2.fd
export FLDTBLDIR=/enduro/tst1/tuxfbuf
export NDRX_DMNLEV=5
export NDRX_DMNLOG=/enduro/tst1/tmp/NDRXD
export NDRX_APPHOME=/enduro/tst1
export NDRX_CLUSTERISED=0
export NDRX_CMDWAIT=1
export NDRX_CONFIG=/enduro/tst1/conf/ndrxconfig.xml
export NDRX_DEBUG_CONF=/enduro/tst1/conf/ndrxdebug.conf
export NDRX_DPID=/enduro/tst1/tmp/ndrxd.pid
export NDRX_DQMAX=3000
export NDRX_HOME=/opt/endurox
export NDRX_IPCKEY=442000
export NDRX_LDBAL=0
export NDRX_LEV=5
export NDRX_LOG=/enduro/tst1/tmp/XADMIN
export NDRX_MSGMAX=100
export NDRX_MSGSIZEMAX=32000
export NDRX_NODEID=1
export NDRX_QPATH=/dev/mqueue
export NDRX_QPREFIX=/tst1
export NDRX_RNDK=jaUZwOlTqglSc
export NDRX_SHMPATH=/dev/shm
export NDRX_SRVMAX=10000
export NDRX_SVCMAX=600
export NDRX_TOUT=60
export NDRX_UBFMAXFLDS=16000
export NDRX_ULOG=/enduro/tst1/logs

# XA 2PC SECTION, ORACLE DB
export ORACLE_SID=ROCKY
export ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1
export PATH=$PATH:ORACLE_HOME/bin
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$ORACLE_HOME/lib
export NDRX_XA_RES_ID=1
export NDRX_XA_OPEN_STR="ORACLE_XA+SqlNet=ROCKY+ACC=P/endurotest/endurotest1+SesTM=180+ ↵
    LogDir=/tmp/xa+nolocal=f"
export NDRX_XA_CLOSE_STR=$NDRX_XA_OPEN_STR

# XA Static registration driver
export NDRX_XA_DRIVERLIB=$NDRX_HOME/lib/libndrxxaoras.so
```



```
# XA Dynamic registration driver
#export NDRX_XA_DRIVERLIB=$NDRX_HOME/lib/libndrxxaorad.so

export NDRX_XA_RMLIB=/u01/app/oracle/product/11.2.0/dbhome_1/lib/libclntsh.so.11.1
export NDRX_XA_LAZY_INIT=1
# XA SECTION, END
```

Common-config ini file sample configuration, assuming following settings in env:

```
export NDRX_CCONFIG=/enduro/tst1/conf/app.ini
export NDRX_CCTAG=server1/RM2
```

The configuration file might look like:

```
#
# Common variables, inherited for CCTAGs
#
[@global]
FIELDTBLS=Exfields,fieldtab1.fd,fieldtab2.fd
FLDTBLDIR=/enduro/tst1/tuxfbuf
NDRX_DMNLEV=5
NDRX_DMNLOG=/enduro/tst1/tmp/NDRXD
NDRX_APPHOME=/enduro/tst1
NDRX_CLUSTERISED=0
NDRX_CMDWAIT=1
NDRX_DPID=/enduro/tst1/tmp/ndrxd.pid
NDRX_DQMAX=3000
NDRX_HOME=/opt/endurox
NDRX_IPCKEY=442000
NDRX_LDBAL=0
NDRX_LEV=5
NDRX_LOG=/enduro/tst1/tmp/XADMIN
NDRX_MSGMAX=100
NDRX_MSGSIZEMAX=32000
NDRX_NODEID=1
NDRX_QPATH=/dev/mqueue
NDRX_QPREFIX=/tst1
NDRX_RNDK=jaUZwOlTqglSc
NDRX_SHMPATH=/dev/shm
NDRX_SRVMAX=10000
NDRX_SVCMAX=600
NDRX_TOUT=60
NDRX_UBFMAXFLDS=16000
NDRX_ULOG=/enduro/tst1/logs

#
# CCTAG section server1
#
[@global/server1]
NDRX_CONFIG=/enduro/tst1/conf/ndrxconfig.xml

#
# CCTAG section RM2
#
[@global/RM2]
# XA 2PC SECTION, ORACLE DB
ORACLE_SID=ROCKY
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1
PATH=$PATH:ORACLE_HOME/bin
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$ORACLE_HOME/lib
NDRX_XA_RES_ID=1
```

```
NDRX_XA_OPEN_STR="ORACLE_XA+SqlNet=ROCKY+ACC=P/endurotest/endurotest1+SesTM=180+LogDir=/tmp ↵
/xa+nolocal=f"
NDRX_XA_CLOSE_STR=$NDRX_XA_OPEN_STR
# XA Static registration driver
NDRX_XA_DRIVERLIB=$NDRX_HOME/lib/libndrxxaoras.so
# XA Dynamic registration driver
#NDRX_XA_DRIVERLIB=$NDRX_HOME/lib/libndrxxaorad.so
NDRX_XA_RMLIB=/u01/app/oracle/product/11.2.0/dbhome_1/lib/libclntsh.so.11.1
NDRX_XA_LAZY_INIT=1
# XA SECTION, END

#
# Debug section (no need for NDRX_DEBUG_CONF in CConfig case)
#
[@debug]
*= ndrxx=0 ubf=0

[@debug/server1]
*= ndrxx=5 ubf=0
```

Chapter 4

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 5

SEE ALSO

`xadmin(8)`, `ndrxd(8)`, `ndrxconfig.xml(5)`, `ndrxdebug.conf(5)`

Chapter 6

AUTHOR

Enduro/X is created by Madars Vitolins.

Chapter 7

COPYING

© Madars Vitolins