

EX_ENVOVER(5)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|--------------------|----------|
| 1 | DESCRIPTION | 1 |
| 2 | SYNOPSIS | 2 |
| 3 | PARAMTERS | 3 |
| 4 | EXAMPLE | 4 |
| 5 | BUGS | 5 |
| 6 | SEE ALSO | 6 |
| 7 | AUTHOR | 7 |
| 8 | COPYING | 8 |

Chapter 1

DESCRIPTION

This is simple text file with shell like syntax for environment variable setup. Used for per ATMI server environment process environment variable override. File is configured in **ndrxconfig.xml(5)** config file.

Chapter 2

SYNOPSIS

Configuration file syntax:

```
# this line is commented
export PARAM_NAME=VALUE
#
PARAM_NAME_2=PARAM_VALUE_2
```

Chapter 3

PARAMTERS

PARAM_NAME

Name of the of the environment variable to be overridden.

VALUE

The value to be used. The value starting from = is directly loaded into memory. All symbols up till end of the line are used.

Chapter 4

EXAMPLE

Sample configuration:

```
#
# This is environment override file for tpevsrv
#

# Syntax is following:
# # = comment
# [export ] = ignored
# ENV_VAR = name of env
# = = equals sign
# VALUE

# Just for test, we set not clusterized
export NDRX_CLUSTERISED=0

# Also for testing se set wrong node id.
NDRX_NODEID=9
```

Chapter 5

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 6

SEE ALSO

xadmin(8), ndrxd(8), ndrconfig.xml(5), ndrdebug.conf(5), ndrconfig.xml(5)

Chapter 7

AUTHOR

EnduroX is created by Madars Vitolins.

Chapter 8

COPYING

© Madars Vitolins