

**EX\_ENVOVER(5)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>PARAMTERS</b>	<b>3</b>
<b>4</b>	<b>EXAMPLE</b>	<b>4</b>
<b>5</b>	<b>BUGS</b>	<b>5</b>
<b>6</b>	<b>SEE ALSO</b>	<b>6</b>
<b>7</b>	<b>COPYING</b>	<b>7</b>

## Chapter 1

# SYNOPSIS

Configuration file syntax:

```
# this line is commented
export PARAM_NAME=VALUE
#
PARAM_NAME_2=PARAM_VALUE_2
```

---

## Chapter 2

# DESCRIPTION

This is simple text file with shell like syntax for environment variable setup. Used for per ATMI server environment process environment variable override. File is configured in **ndrxconfig.xml(5)** config file.

## Chapter 3

# PARAMTERS

**PARAM\_NAME**

Name of the of the environment variable to be overridden.

**VALUE**

The value to be used. The value starting from = is directly loaded into memory. All symbols up till end of the line are used.

---

## Chapter 4

# EXAMPLE

Sample configuration:

```
#
# This is environment override file for tpevsrv
#

# Syntax is following:
# # = comment
# [export ] = ignored
# ENV_VAR = name of env
# = = equals sign
# VALUE

# Just for test, we set not clusterized
export NDRX_CLUSTERISED=0

# Also for testing se set wrong node id.
NDRX_NODEID=9
```

## Chapter 5

# BUGS

Report bugs to © Mavimax, Ltd



## Chapter 6

## SEE ALSO

`xadmin(8)`, `ndrxd(8)`, `ndrxconfig.xml(5)`, `ndrxdebug.conf(5)`, `ndrxconfig.xml(5)`

## **Chapter 7**

# **COPYING**

© Mavimax, Ltd