

TPFREECTXT(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <atmi.h>
```

```
void tpfreetxt(TPCONTEXT_T context);
```

Link with *-latmisrv|-latmisrvnomain|-latmisrvinteg -latmi -lubf -lnstd -lpthread -lrt -lm*

Chapter 2

DESCRIPTION

Function frees up the context data which was returned by **tpgetctxt(3)** function call. Function does not do the **tpterm(3)**. Thus to remove context data fully, firstly thread running with context must call **tpterm(3)**, then **tpgetctxt(3)** and then call **tpfreectxt()**.

This function uses underlying thread local storage infrastructure which is provided separately for each of the major Enduro/X libraries - libnstd (Standard library), libufb (UBF buffer library) and libatmi (ATMI library). If operations at library levels are required, then following functions can be used:

1. **ndrx_nstd_tls_new()**, **ndrx_ufb_tls_new()**, **ndrx_atmi_tls_new()** - allocate TLS data for library.
 2. **ndrx_nstd_tls_get()**, **ndrx_ufb_tls_get()**, **ndrx_atmi_tls_get()** - get the TLS data for library (currently associated with thread).
 3. **ndrx_nstd_tls_set()**, **ndrx_ufb_tls_set()**, **ndrx_atmi_tls_set()** - set the thread local data from saved pointer.
 4. **ndrx_nstd_tls_free()**, **ndrx_ufb_tls_free()**, **ndrx_atmi_tls_free()** - free the thread local data.
-

Chapter 3

RETURN VALUE

N/A

Chapter 4

ERRORS

N/A

Chapter 5

EXAMPLE

See `atmitest/test016_contextsw/atmict16.c` for sample code.

Chapter 6

BUGS

Report bugs to madars.vitolins@gmail.com

Chapter 7

SEE ALSO

`tpgetctx(3)` `tpsetctx(3)` `tpsrvsetctxdata(3)` `tpsrvgetctxdata(3)` `tpcontinue(3)` `tpinit(3)`

Chapter 8

COPYING

© Mavimax, Ltd