

BFNAME(3)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SYNOPSIS	1
2	DESCRIPTION	2
3	RETURN VALUE	3
4	ERRORS	4
5	EXAMPLE	5
6	BUGS	6
7	SEE ALSO	7
8	COPYING	8

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
char * Bfname (BFLDID bflidid);
```

```
Link with -lubf -lnstd -lm -lpthread
```


Chapter 2

DESCRIPTION

Return the field name loaded for given compiled field id *bflid*. Field id is compiled by **mkfldhdr(8)**.

Chapter 3

RETURN VALUE

On success, **Bfname()** returns field name in thread local storage stored char array. If field is unknown to the system, function returns NULL and the error is set.

Chapter 4

ERRORS

In case of error **Berror** will be non **0**. Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

BBADFLD field not found in field tables.

Chapter 5

EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

Chapter 6

BUGS

Report bugs to support@mavimax.com

Chapter 7

SEE ALSO

Bfldid(3)

Chapter 8

COPYING

© Mavimax, Ltd