

**BPRINT(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>ERRORS</b>	<b>4</b>
<b>5</b>	<b>EXAMPLE</b>	<b>5</b>
<b>6</b>	<b>BUGS</b>	<b>6</b>
<b>7</b>	<b>SEE ALSO</b>	<b>7</b>
<b>8</b>	<b>COPYING</b>	<b>8</b>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
int Bprint (UBFH *p_ub);
```

Link with *-lubf -lnstd -lm -lpthread*

## Chapter 2

# DESCRIPTION

Function prints the *p\_ub* buffer content to **stdout**. The format of the output is "<FIELD><TAB><VALUE><NEW LINE>". The **BFLD\_CARRAY** fields are printed in the way that non readable characters are printed in hex-decimal format, prefixed with \. If value contains \ char, then it is printed as \\. Example:

```
T_SHORT_FLD      1765
T_LONG_FLD       3333111
T_LONG_FLD       2
T_CHAR_FLD       A
T_FLOAT_FLD      1.33000
T_DOUBLE_FLD     1111.220000
T_DOUBLE_FLD     333.000000
T_DOUBLE_FLD     444.000000
T_STRING_FLD     HELLO WORLD
T_CARRAY_FLD     \00\01\02\03HELLO BINARY\04\05\00
```

Floating point values are printed with 6 symbols after decimal separator.

## Chapter 3

# RETURN VALUE

On success, **Bprint()** return zero; on error, -1 is returned, with **Berror** set to indicate the error.

## Chapter 4

# ERRORS

Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BALIGNERR** Corrupted buffer or pointing to not aligned memory area.

**BNOTFLD** Buffer not fielded, not correctly allocated or corrupted.

---

## Chapter 5

# EXAMPLE

See `ubftest/test_print.c` for sample code.

## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

## Chapter 7

## SEE ALSO

**Bextread(3) Bfprint(3) Bfprintcb(3) \*Bread(3) Bwrite(3)**

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd