

**BFNAME(3)**

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>SYNOPSIS</b>	<b>1</b>
<b>2</b>	<b>DESCRIPTION</b>	<b>2</b>
<b>3</b>	<b>RETURN VALUE</b>	<b>3</b>
<b>4</b>	<b>ERRORS</b>	<b>4</b>
<b>5</b>	<b>EXAMPLE</b>	<b>5</b>
<b>6</b>	<b>BUGS</b>	<b>6</b>
<b>7</b>	<b>SEE ALSO</b>	<b>7</b>
<b>8</b>	<b>COPYING</b>	<b>8</b>

## Chapter 1

# SYNOPSIS

```
#include <ubf.h>
```

```
char * Bfname (BFLDID bflidid);
```

```
Link with -lubf -lnstd -lm -lpthread
```

## Chapter 2

# DESCRIPTION

Return the field name loaded for given compiled field id *bflid*. Field id is compiled by **mkfldhdr(8)**.

## Chapter 3

# RETURN VALUE

On success, **Bfname()** returns field name in thread local storage stored char array. If field is unknown to the system, function returns NULL and the error is set.

## Chapter 4

# ERRORS

In case of error **Berror** will be non **0**. Note that **Bsterror()** returns generic error message plus custom message with debug info from last function call.

**BBADFLD** field not found in field tables.

---

## Chapter 5

# EXAMPLE

See `ubftest/ubfunit1.c` for sample code.

## Chapter 6

# BUGS

Report bugs to [support@mavimax.com](mailto:support@mavimax.com)

# Chapter 7

# SEE ALSO

Bfldid(3)

## **Chapter 8**

# **COPYING**

© Mavimax, Ltd