

BFLDDBUNLOAD(3)

| REVISION HISTORY | | | |
|------------------|------|-------------|------|
| NUMBER | DATE | DESCRIPTION | NAME |
| | | | |

Contents

| | | |
|----------|---------------------|----------|
| 1 | SYNOPSIS | 1 |
| 2 | DESCRIPTION | 2 |
| 3 | RETURN VALUE | 3 |
| 4 | EXAMPLE | 4 |
| 5 | BUGS | 5 |
| 6 | SEE ALSO | 6 |
| 7 | COPYING | 7 |

Chapter 1

SYNOPSIS

```
#include <ubf.h>
```

```
void Bflddbunload(void);
```

Link with *-lubf -lnstd -lm -lpthread*

Chapter 2

DESCRIPTION

Function closes LMDB handlers which are open for custom field database. Function is not thread safe in respect to other Bflddb* functions.

If DB is already closed, then function will do nothing.

Currently Enduro/X at process exist does not unload the database handles. It is expected that OS will free any IPC (semaphores) automatically.

Chapter 3

RETURN VALUE

There is no return value.

Chapter 4

EXAMPLE

See `atmitest/test050_ubfdb/atmiclt50.c` for sample code.

Chapter 5

BUGS

Report bugs to support@mavimax.com

Chapter 6

SEE ALSO

Bfddbaid(3) Bfddbname(3) Bfddbload(3) Bfddbunlink(3) Bfddbdrop(3) Bfddbdel(3) Bfddbadd(3) Bfddbget(3) ubfdb.ini(5)

Chapter 7

COPYING

© Mavimax, Ltd